

Expo Exterior Fastpatch



DESCRIPTION

USE:

An easy to use, fast setting and non-shrinking patch material for exterior plaster. This quick-setting product should be used within 15 to 20 minutes after mixing.

COVERAGE:

Coverage will vary with applied thickness: approximately 6 square feet when applied 7/8-inch thick per 50 pound bag.

COMPOSITION:

Expo Exterior Fast Patch is a mechanically blended compound of portland cement, inert aggregates and proprietary additives, packed in sealed water-resistant multi-wall bags.

ADVANTAGES:

The quick setting characteristics of Expo Exterior Fast Patch enables rapid completion of the job. The product is blended to allow easy duplication of a stucco sand finish.

SHELF LIFE:

Six (6) months if kept in dry condition.

JOB PROCEDURE

SUBSTRATE:

Area to be patched should be free of loose material and dust. Dampen area to be patched before applying.

MIXING:

Mix product thoroughly with clean water to a trowelable consistency.

APPLICATION:

Large holes should first be patched with a scratch coat, followed by a finish coat after the scratch coat takes up. Small holes may be patched in one step.

NOTE:

Expo Exterior Fast Patch should not be retempered.

MATERIAL STANDARDS:

Portland cement: Type 1 A.S.T.M. Designation C150-56, Federal Specification SSS-C-192B. Hydrated Lime: Federal Specification SS-L-351B, Type F and Type M, A.S.T.M. Designations C206-84 (Type S) and C207-79 (Type S), U.B.C. Standard No. 24-18-82.